



Product Datasheet: Link Seal® Modular Seal


Link-Seal® Modular Seals are the premier method for permanently sealing pipes of any size passing through walls, floors and ceilings. In fact, any cylindrical object may be quickly, easily and permanently sealed, as they pass through barriers.

FEATURES

- · Saves money and time
- Positive hydrostatic seal
- Long seal life
- Maximum protection against corrosion
- Oil, jet fuel, fire resistant and high temperature resistant material available
- Modular: configure seal to match your application



THE PRINCIPLE



The radial expansion of the rubber ensures the hydrostatic pressure tightness



MATERIAL PROPERTIES

Temperature resistance Standard version black -40° C up to +80° C

Type T, grey -55° C up to $+230^{\circ}$ C Type O, green -40° C up to $+70^{\circ}$ C

Oil, jet fuel resistance Type O

Version for plastic pipes Blue EPDM Shore 40 ± 5

Up to 3 bar (Lloyd's registered) Original Link-Seal® Type BC

and BS316

Up to 2 bar (Lloyd's registered) Type S-LS

Cathodic protection Dielectrical strength 500 V/mm

APPLICATIONS: Buildings, Tanks, Bunds - use Link-Seal anywhere a pipe passes through a

barrier







- 1. Link-Seal is shipped as a belt of interconnecting rubber links
- 2. Wrap the belt around the pipe and connect the first and last links together



1



- 3. Slide the assembly into the space between the pipe and wall opening
- 4. When the bolts are tightened, Link-Seal expands to create a gas and water tight seal



3



Anode Engineering 30 Chetwynd Street

30 Chetwynd Street Loganholme QLD 4129 AUSTRALIA Ph:+61 7 3801 5521

Email: Sales@Anodeengineering.com

www.Anodeengineering.com

Lordco

59-61 Marsden Street Lower Hutt, Wellington 5045 NEW ZEALAND Ph:+64 4 939 3944

Email: Sales@Lordco.co.nz

www.Lordco.co.nz