

Casing Isolators and End Seals

Link-Seal® Modular Seals



Link-Seal® Modular Seals are the premier method for permanently sealing pipes of any size passing through walls, floors and ceilings. In fact, any cylindrical object may be quickly, easily and permanently sealed, as they pass through barriers.

FEATURES:

- Saves money and time
- Positive hydrostatic seal
- Long seal life
- Maximum protection against corrosion
- Oil, jet fuel, fire resistant and high temperature resistant material available
- Modular: configure seal to match your application



THE PRINCIPLE:

The radial expansion of the Link-Seal Modular Seals rubber ensures the hydrostatic pressure tightness.



MATERIAL PROPERTIES:

Temperature resistance	Standard version black	-40° C up to +80° C
	Type T, grey	-55° C up to +230° C
	Type O, green	-40° C up to +70° C
Oil, jet fuel resistance	Type O	
Version for plastic pipes	Blue EPDM	Shore 40 ± 5
Pressure tightness	Up to 5 bar (TÜV and Lloyd's registered) Original Link-Seal®	
	Up to 3 bar (Lloyd's registered) Original Link-Seal® Type BC and BS316	
	Up to 2 bar (Lloyd's registered) Type S-LS	
Cathodic protection	Dielectrical strength 500 V/mm	

APPLICATIONS: Buildings, Tanks, Bunds - use Link-Seal anywhere a pipe passes through a barrier.

Casing Isolators and End Seals

Link-Seal® Modular Seals



PIPELINE



ELECTRICAL



INDUSTRIAL



MARINE



MONITORING



1. Link-Seal is shipped as a belt of interconnecting rubber links.



2. Wrap the belt around the pipe and connect the first and last links together.



3. Slide the assembly into the space between the pipe and wall opening.



4. When the bolts are tightened, Link-Seal expands to create a gas and water tight seal.



Please contact us for a quotation.